



Aerolube Technologies



Technical Data Sheet

8013 Battery Terminal Protector **Anti-Sulfation Coating**

Product Description

Stanvac 8013 Battery Terminal Coating Waxy is an acid resistant corrosion inhibitor for providing long term protection for battery terminals. It is highly resistant to high humidity and salt spray and forms a protective waxy shield against rust, moisture, heat and corrosive influences. It is safe for use on all metals, rubbers, plastics and paint finishes and is ideal for use as a heavy-duty corrosion protective coating.

Stanvac 8013 Battery Terminal Coating is a safe nontoxic formulation and does not contain any chlorinated solvents, CFCs or any ozone depleting substances.

Applications

It is effective for protection of battery terminals, clamps in all types of automobile, industrial, aircraft and marine batteries.

Benefits

- Waxy, acid resistant film completely seals out moisture
- Protects battery and cable terminals from corrosion and acid sulfation
- Heavy duty corrosion inhibiting film assures complete rust protection and prolongs battery life
- Highly resistant to humidity & salt spray and offers long lasting protection
- Provides long term corrosion protection up to 1 year
- Translucent reddish brown color provides easy visual inspection
- Maximizes performance & reliability of equipment
- Soft, waxy, pliable coating does not crack or peel even under severe operating conditions as heat, vibratory shocks, weathering influences
- Prevents hard starting, current loss and battery failure by assuring continual voltage output

Directions For Use

Remove existing residues by cleaning with Stanvac 8012 Battery Terminal Cleaner prior to applying this coating for optimum performance and longer battery life. Shake can well before use. Repeat the same before every application. Spray from a distance of 8 to 12 inches and allow few minutes for solvents to evaporate. Do not wipe off. Reapply regularly for optimum battery life. Do not apply on energized equipment. Prevent aerosol can contact with the battery terminals.

Caution Contains flammable solvents and propellant. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Aerolube Technologies

A-501, Kabra Centroid, 168/169, Vidyanagari Marg, Kalina, Santacruz (E), Mumbai - 400 098. Mobile : 93200 01540

E-mail : sales@aerolubeindia.com | aerolubetech@rediffmail.com | Website : www.aerolubeindia.com



8013 Battery Terminal Protector Anti-Sulfation Coating

TECHNICAL PROPERTIES	
Parameter*	Value
Type	Heavy duty corrosion inhibitor
Color	Translucent reddish brown
Odor	Mild petroleum
Appearance	Waxy film
Specific Gravity @ 20°C	0.85-0.90 g/cm ³
Flash Point	-18°C (aerosol)
Temperature Range, °C	-40 to +100
Vapor Pressure (air =1)	>air
Salt Spray Test (5%Solution)	+300 hours
Humidity Cabinet Test	+300 hours
Special Properties	Highly resistant to high humidity, moisture, water, chemicals, salt spray, oxidation.
Propellant	Non CFC

* of active ingredients

Available Packaging

500 ml Aerosol Spray

Shelf Life

24 months from date of manufacture in sealed condition.

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from Aerolube or your local Aerolube distributor.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended Stanvac product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

Aerolube Technologies