



**Aerolube Technologies**



### Technical Data Sheet

## **GEARTECH OGL 2500/000**

### **High Performance Sprayable Grease For Lubrication of Open Gears**

#### Product Description

Stanvac Geartech OGL 2500/000 is a non-hardening, sprayable, adhesive grease designed for lubrication and protection of tooth flanks of large open gears exposed to extremely high loads and temperatures.

Stanvac Geartech OGL 2500/000 is based on highly viscous mineral oils thickened with an aluminum complex soap thickener with a high content of ultra-fine graphite and select extreme pressure and anti-wear additives.

Stanvac Geartech OGL 2500/000 ensures excellent resistance to shock loading and prevents danger of damage to tooth flanks by continually maintaining a boundary lubricating film between frictional points of mating surfaces.

Stanvac Geartech OGL 2500/000 clings tenaciously to gear tooth flanks and does not squeeze out under high loads and pressures.

Stanvac Geartech OGL 2500/000 is capable of withstanding extreme operating and environmental conditions and protects surface from corrosion and can be easily pumped via spray systems on to the gear teeth.

#### Application

For spray lubrication of open gears in:

- Heavy engineering industries, Cement, gypsum and lime manufacturing equipment, Mining and earth moving equipment, Wood working equipment, Sugar mill machinery

For lubrication and wear protection of:

- Highly stressed large open gears and slew ring gears, Large chains, Wire ropes, Guide rails

#### Benefits

- Wide service temperature range of +5°C to +180°C
- Thermally stable within -30°C+250°C
- Excellent adhesion to metal surfaces
- Forms a non-hardening, adhesive film over gear tooth flanks capable of withstanding high pressures
- Excellent load carrying capacity under severe conditions
- Very good resistance to water and water washout
- Contains additives to prevent against degradation by rust, corrosion and oxidation
- Easily sprayable through spraying systems
- Free of bitumen, chlorine, lead, toxic heavy metals or hazardous solvents

#### Directions for Use

Use as supplied. Never dilute or mix with oil or grease. Apply on all clean sliding surfaces by normal greasing methods i.e. by brush, grease gun or dispense via centralized lubrication systems. Replace cover after use.

#### General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

#### Available Packaging

180 Kg

#### Shelf Life

36 months from date of manufacture in sealed condition.

### **Aerolube Technologies**

A-501, Kabra Centroid, 168/169, Vidyanagari Marg, Kalina, Santacruz (E), Mumbai - 400 098. Mobile : 93200 01540

E-mail : [sales@aerolubeindia.com](mailto:sales@aerolubeindia.com) | [aerolubetech@rediffmail.com](mailto:aerolubetech@rediffmail.com) | Website : [www.aerolubeindia.com](http://www.aerolubeindia.com)



**Aerolube Technologies**



## **GEARTECH OGL 2500/00**

**High Performance Sprayable Grease For Lubrication of Open Gears**

| TECHNICAL PROPERTIES        |  |                    |             |
|-----------------------------|--|--------------------|-------------|
| PARAMETER                   | VALUE                                  | UNIT               | METHOD      |
| Appearance                  | Smooth grease                          |                    | Visual      |
| Color                       | Black                                  |                    | Visual      |
| Base oil                    | Mineral / synthetic                    |                    | In house    |
| Base oil viscosity @ 40°C   | ~3200                                  | mm <sup>2</sup> /s | ASTM D 445  |
| Thickener                   | Aluminum complex                       |                    | In house    |
| Penetration, worked         | 445-475                                | mm/10              | ASTM D 217  |
| NLGI consistency            | 000                                    | Class              | DIN 51 818  |
| Water washout               | <1                                     | % wt. loss         | ASTM D 1264 |
| Copper strip corrosion      | 1b                                     | Rating             | ASTM D 4048 |
| Rust prevention             | Pass                                   |                    | ASTM D 1743 |
| Lubricating solid           | Ultrafine graphite                     |                    | In house    |
| Four ball test, weld load   | 800                                    | kg                 | ASTM D 2596 |
| FZG test, damage load stage | ≥12                                    |                    | DIN 51 354  |
| Service temperatures        | +5 to +180 (thermal stability to +250) | °C                 |             |

### Disposal

All used and unused product should be disposed of in accordance with state regulations.

### Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from Aerolube or your local Aerolube distributor.

### Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended Stanvac product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

### **Aerolube Technologies**

A-501, Kabra Centroid, 168/169, Vidyanagari Marg, Kalina, Santacruz (E), Mumbai - 400 098. Mobile : 93200 01540  
E-mail : [sales@aerolubeindia.com](mailto:sales@aerolubeindia.com) | [aerolubetech@rediffmail.com](mailto:aerolubetech@rediffmail.com) | Website : [www.aerolubeindia.com](http://www.aerolubeindia.com)