



**Aerolube Technologies**



### Technical Data Sheet

## **Siltech 1000 HVG Stiff, Non-Melting Silicone Grease Like Compound For Use as a valve Lubricant Cum Sealant**

### Applications

- Lubricant for O-rings, packings, rubbers, gaskets, miniature bearing seals to provide resistance to water, chemicals, oxidation and provide thermal stability
- Lubrication of pneumatic control valves, fire extinguishers and water softener valves
- Sealant and lubricant for glass joints and stopcocks in normal as well as high vacuum systems
- Lubricant for pressure lubricated plug valves, flow meter bearings, ceramic plug cocks
- Sealant for vacuum and pressure systems
- Sealant between synthetic rubber or plastic parts to prevent them from sticking in vacuum or pressure systems
- Chemical barrier and resistant coating for chemical processing equipment
- Damping media for dash pots in electrical and electronic equipment
- Assembly agent for holding rubbers and other parts due to its highly tacky nature
- All ingredients comply with regulations for food grade materials

### Benefits

- Wide service temperature range from -40°C to +200°C
- Very good oxidation resistance
- Completely resistant to water, steam, humidity and corrosives
- Low vapor pressure and low volatility
- Compatible with plastics, rubbers, elastomers, and other gasketing and O-ring seal materials
- Prevents age hardening, stress cracking and maintains resilience of plastics
- Non gumming, non melting and non toxic
- Provides good lubricating and sealing properties for rubbers and plastics
- Chemically inert and resistant to most chemicals, hot and cold water, vegetable and mineral oils, dilute acids and alkalis, glycerin, ethanol, methanol, butane, steam, natural gas, ethylene glycol, most organic and inorganic chemicals and aqueous solutions.

### Directions for Use

Use as supplied. Never dilute or mix with other oil or grease. Apply by means of hand, brush or putty knife. Can also be dispersed in solvents like mineral spirits, xylene or methyl ethyl ketone for thinning the consistency and making it easier to apply by brushing, dipping or spraying.

### General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

### Available Packaging

1 Kg, 5 Kg

### Shelf Life

36 months from date of manufacture in sealed condition.

## **Aerolube Technologies**

A-501, Kabra Centroid, 168/169, Vidyanagari Marg, Kalina, Santacruz (E), Mumbai - 400 098. Mobile : 93200 01540  
E-mail : [sales@aerolubeindia.com](mailto:sales@aerolubeindia.com) | [aerolubetech@rediffmail.com](mailto:aerolubetech@rediffmail.com) | Website : [www.aerolubeindia.com](http://www.aerolubeindia.com)



## Siltech 1000 HVG Stiff, Non-Melting Silicone Grease Like Compound For Use as a valve Lubricant Cum Sealant

### TECHNICAL PROPERTY

Parameter	Value	Unit	Standard
Type	Silicone compound		
Appearance	Smooth stiff consistency grease		
Base oil	Silicone		
Thickener	Inorganic		
Color <sup>1</sup>	White, translucent		
Penetration, - Unworked - Worked, 60 strokes	180-210 200-220	mm/10	ASTM D 217
NLGI consistency	3	Class	DIN 51 818
Density, @ 25°C	1	g/cm <sup>3</sup>	
Drop point	None	°C	ASTM D 566
Service temperatures	-40 to +200	°C	
Water resistance, static evaluation	0-90		DIN 51 807 pt.1
Evaporation loss, 24h, 200°C	2 max	%	
Oil separation, standard test	<3.5	%	DIN 51 817
Bleed, 24h, 200°C	<0.1 max	%	

1. Minor color variation of the same product but of different batches could be possible. However the lubrication values remain unchanged.

### Disposal

All used and unused product should be disposed of in accordance with state regulations.

### Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from Aerolube or your local Aerolube distributor.

### Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended Stanvac product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.